

\* Click the series number to check the product information

## Control Button, Stick

### FPC/FFC Connectors

Height: 0.85~5.32mm



● 0.5mm Pitch

**6809** Ease of use, Robust, Front-lock

**6811** Robust, Front-lock

**6284** Non-ZIF

**6806** Ease of use, Front-lock

**6892** AOI-compatible, Front-lock

**6244** Vertical, Non-ZIF

## Battery

### Board to Board Connectors

Stacking Height: 0.7mm



● 0.35mm Pitch

**7129** Power 10A

## Speaker, Mic., Sensor

### FPC/FFC Connectors

Height: 0.85~1.75mm



● 0.3mm Pitch

**6293** Lower-profile, Back-lock

**6844** Space-saving, Front-lock

● 0.4mm Pitch

**6824** Space-saving, Non-ZIF

● 0.5mm Pitch

**6277** Low pin count, Back-lock

**6298** Low pin count, Back-lock

**6809** Ease of use, Robust, Front-lock

**6811** Robust, Front-lock

**6284** Non-ZIF

**6806** Ease of use, Front-lock

### Board to Board Connectors

Stacking Height: 0.6~2.0mm



● 0.35mm Pitch

**7129** Power 10A

**5861** Power 5A, Lower-profile

**5843** Stacking height variations

● 0.4mm Pitch

**5804** Stacking height variations

## Vibrator

### Wire to Board Connectors

Height: 0.9~3.61mm



**8041** 0.9mm Pitch


**8040** 1.0mm Pitch

**8005** 1.27mm Pitch

## Main – Sub. PCB (I/O)

### FPC/FFC Connectors

Height: 0.85~5.32mm



● 0.3mm Pitch

**6293** Lower-profile, Back-lock

**6844** Space-saving, Front-lock

● 0.4mm Pitch

**6824** Space-saving, Non-ZIF

● 0.5mm Pitch

**6809** Ease of use, Robust, Front-lock

**6811** Robust, Front-lock

**6284** Non-ZIF

**6806** Ease of use, Front-lock

**6892** AOI-compatible, Front-lock

**6244** Vertical, Non-ZIF