

* Click the series number to check the product information

Button, Speaker, Mic., Sensor

FPC/FFC Connectors

Height: 0.85~2.2mm



- 0.2mm Pitch
6866 Space-saving, Front-lock
- 0.3mm Pitch
6293 Lower-profile, Back-lock
6844 Space-saving, Front-lock
- 0.4mm Pitch
6824 Space-saving, Non-ZIF
- ● 0.5mm Pitch
6277 Low pin count, Back-lock
6298 Low pin count, Back-lock
6809 Ease of use, Robust, Front-lock
6811 Robust, Front-lock
6284 Non-ZIF
6806 Ease of use, Front-lock
6892 AOI-compatible, Front-lock

Board to Board Connectors

Stacking Height: 0.6~2.0mm



- 0.35mm Pitch
5811 Power 3A, Space-saving
7129 Power 10A
5861 Power 5A, Lower-profile
5843 Stacking height variations
- 0.4mm Pitch
5804 Stacking height variations

Main – Sub. PCB, Display

FPC/FFC Connectors

Height: 0.85~2.2mm



- 0.2mm Pitch
6866 Space-saving, Front-lock
- 0.3mm Pitch
6293 Lower-profile, Back-lock
6844 Space-saving, Front-lock
- 0.5mm Pitch
6809 Ease of use, Robust, Front-lock
6811 Robust, Front-lock
6284 Non-ZIF
6806 Ease of use, Front-lock
6892 AOI-compatible, Front-lock

Board to Board Connectors

Stacking Height: 0.6~2.0mm



- 0.35mm Pitch
5861 Power 5A, Lower-profile
5863 Power 5A
5897 Power 3A, High pin count
5843 Stacking height variations
- 0.4mm Pitch
5804 Stacking height variations

Vibrator

Wire to Board Connectors

Height: 0.9~3.61mm



- 8041** 0.9mm Pitch
- 8040** 1.0mm Pitch
- 8005** 1.27mm Pitch

Battery

Board to Board Connectors

Stacking Height: 0.6~0.7mm



- 0.35mm Pitch
5811 Power 3A, Space-saving
7129 Power 10A