


\* Click the series number to check the product information

### Sub. PCB (Disk Drive)

#### FPC/FFC Connectors

Height: 0.85~2.2mm



- 0.2mm Pitch  
**6866** Space-saving, Front-lock
- 0.3mm Pitch  
**6293** Lower-profile, Back-lock  
**6844** Space-saving, Front-lock
- 0.4mm Pitch  
**6824** Space-saving, Non-ZIF
- 0.5mm Pitch  
**6809** Ease of use, Robust, Front-lock  
**6811** Robust, Front-lock  
**6284** Non-ZIF  
**6806** Ease of use, Front-lock  
**6892** AOI-compatible, Front-lock

### Shield Case

#### Shield Locks

Height: 1.8, 3.0mm




**8069** Better work efficiency

### Main – Sub. PCB (I/O)

#### FPC/FFC Connectors

Height: 0.85~5.32mm



- 0.2mm Pitch  
**6866** Space-saving, Front-lock
- 0.3mm Pitch  
**6293** Lower-profile, Back-lock  
**6844** Space-saving, Front-lock
- 0.4mm Pitch  
**6824** Space-saving, Non-ZIF
- 0.5mm Pitch  
**6809** Ease of use, Robust, Front-lock  
**6811** Robust, Front-lock  
**6284** Non-ZIF  
**6806** Ease of use, Front-lock  
**6892** AOI-compatible, Front-lock  
**6817** One-Action

