


* Click the series number to check the product information

Sub. PCB (Disk Drive)

FPC/FFC Connectors

Height: 0.85~2.2mm



- 0.2mm Pitch
[6866](#) Space-saving, Front-lock
- 0.3mm Pitch
[6293](#) Lower-profile, Back-lock
[6844](#) Space-saving, Front-lock
- 0.4mm Pitch
[6824](#) Space-saving, Non-ZIF
- 0.5mm Pitch
[6809](#) Ease of use, Robust, Front-lock
[6811](#) Robust, Front-lock
[6284](#) Non-ZIF
[6806](#) Ease of use, Front-lock
[6892](#) AOI-compatible, Front-lock

Shield Case

Shield Locks

Height: 1.8, 3.0mm




[8069](#) Better work efficiency

Main – Sub. PCB (I/O)

FPC/FFC Connectors

Height: 0.85~5.32mm



- 0.2mm Pitch
[6866](#) Space-saving, Front-lock
- 0.3mm Pitch
[6293](#) Lower-profile, Back-lock
[6844](#) Space-saving, Front-lock
- 0.4mm Pitch
[6824](#) Space-saving, Non-ZIF
- 0.5mm Pitch
[6809](#) Ease of use, Robust, Front-lock
[6811](#) Robust, Front-lock
[6284](#) Non-ZIF
[6806](#) Ease of use, Front-lock
[6892](#) AOI-compatible, Front-lock
[6817](#) One-Action

