

* Click the series number to check the product information

Battery

FPC/FFC Connectors

Height: 1.5mm



● 0.5mm Pitch

6808 Power 4A, Back-lock

Board to Board Connectors

Stacking Height: 0.6~0.7mm



● 0.35mm Pitch

5811 Power 3A, Space-saving

7129 Power 10A

Main PCB, Display

FPC/FFC Connectors

Height: 0.85~5.45mm



● 0.2mm Pitch

6866 Space-saving, Front-lock

● 0.3mm Pitch

6293 Lower-profile, Back-lock

6844 Space-saving, Front-lock

● 0.5mm Pitch

6277 Low pin count, Back-lock

6298 Low pin count, Back-lock

6809 Ease of use, Robust, Front-lock

6811 Robust, Front-lock


6817 One-Action

6244 Vertical, Non-ZIF

6251 Vertical, Flip-lock

Board to Board Connectors

Stacking Height: 0.6~2.0mm



● 0.35mm Pitch

5861 Power 5A, Lower-profile

5863 Power 5A

5897 Power 3A, High pin count

5843 Stacking height variations

● 0.4mm Pitch

5806 Space-saving

5804 Stacking height variations

Speaker, Mic.

FPC/FFC Connectors

Height: 0.85~0.95mm



● 0.2mm Pitch

6866 Space-saving, Front-lock

● 0.3mm Pitch

6293 Lower-profile, Back-lock

6844 Space-saving, Front-lock

● 0.5mm Pitch

6277 Low pin count, Back-lock

6298 Low pin count, Back-lock

Board to Board Connectors

Stacking Height: 0.6~2.0mm



● 0.35mm Pitch

5861 Power 5A, Lower-profile

5863 Power 5A

5897 Power 3A, High pin count

5843 Stacking height variations

● 0.4mm Pitch

5806 Space-saving

5804 Stacking height variations

Wire to Board Connectors

Height: 0.9~3.61mm



8041 0.9mm Pitch

8040 1.0mm Pitch

8005 1.27mm Pitch