

NO.	DESCRIPTION	PART NO.	QTY	MATERIAL	DRW NO.	REMARKS
1	INSULATOR		1	HEAT RESISTING PLASTIC		COLOR: BLACK UL94V-0
2	CONTACT		N	COPPER-ALLOY		Au, Be-Free
3	ANCHOR PLATE		2	COPPER-ALLOY		Au, Be-Free

極数 NO. OF POS.	A	B	C	D	E	F	G
6	0.70	2.40	3.40	1.80	2.30	1.31	2.82
10	1.40	3.10	4.10	2.50	3.00	2.01	3.52
12	1.75	3.45	4.45	2.85	3.35	2.36	3.87
16	2.45	4.15	5.15	3.55	4.05	3.06	4.57
18	2.80	4.50	5.50	3.90	4.40	3.41	4.92
20	3.15	4.85	5.85	4.25	4.75	3.76	5.27
24	3.85	5.55	6.55	4.95	5.45	4.46	5.97
30	4.90	6.60	7.60	6.00	6.50	5.51	7.02
34	5.60	7.30	8.30	6.70	7.20	6.21	7.72
40	6.65	8.35	9.35	7.75	8.25	7.26	8.77
42	7.00	8.70	9.70	8.10	8.60	7.61	9.12
44	7.35	9.05	10.05	8.45	8.95	7.96	9.47
46	7.70	9.40	10.40	8.80	9.30	8.31	9.82
48	8.05	9.75	10.75	9.15	9.65	8.66	10.17
50	8.40	10.10	11.10	9.50	10.00	9.01	10.52
54	9.10	10.80	11.80	10.20	10.70	9.71	11.22
60	10.15	11.85	12.85	11.25	11.75	10.76	12.27


※この表は1ページ目のみ適用
 ※THIS CHART IS APPLICABLE TO SHEET-1 ONLY.

注記
NOTE

- ① テール及び金具底面の相互の輪郭度は、0.08MAX.
COPLANARITY OF CONTACT TAIL
AND ANCHOR PLATE IS 0.08MAX.
 - ② 図示の位置にLOT NO. を刻印する。(レーザー)
LOT NO. SHALL BE MARKED
AT THE SPECIFIED POSITION. (LASER)
- n S (6P) K n S (10P~18P)
 工場コード 工場コード
 製造週 製造週
 「K」表示(固定)
- K 3 01 S (24P~)
 工場コード
 製造日 1, 2, ~29, 30, 31.
 製造月 1, 2, ~9, X, Y, Z.
 「K」表示(固定)

3. STENCIL LAYOUTは左図を推奨とする。
 尚、MOUNTING LAYOUTに対し
 開口率は70%としている。


※この注記は1ページ目のみ適用
 ※THIS NOTES IS APPLICABLE TO
 SHEET-1 ONLY.



ROHS規制対応
 COMPLIANT WITH
 ROHS REGULATIONS

TOLERANCE / 一般公差(S)		PRODUCT SPEC / 製品規格		P	DCN21556	2021/07/13	K. AZUMA	H. WATANABE	S. HORINO
X < 10	±0.2	UNIT	ANGLE	N	DCN19D12	2019/12/02	K. AZUMA	H. WATANABE	A. TSUNEMURA
10 ≤ X < 30	±0.25	mm	3RD	O	EDN-459	2015/09/15	K. HIRATA	K. YAMANE	T. SASAKI
30 ≤ X	±0.3	SCALE	DATE	NO.	EDN/DCN	DATE	ISSUE	CHECKED	APPROVED
ANGLE / 角度	±3°	NTS	2015/09/15	PART NAME / 品名					
SERIES 5861 PLUG ASSY						0.35mm PITCH BOARD TO BOARD H=0.6			
DRAWN	DESIGNED	CHECKED	APPROVED	PART NO. / 型番					
K. HIRATA	K. HIRATA	K. YAMANE	T. SASAKI	14 5861 XXX 024 829 +					
DWG NO. / 図番				SHEET		REV			
BJS 5861005				11/2		P			

NO.	DESCRIPTION	PART NO.	QTY	MATERIAL	DRW NO.	REMARKS
1	CONNECTOR	14 5861 XXX 024 829 +	15000			10 5861 XXX 024 829 +
2	EMBOSSSED TAPE		1	POLYSTYRENE		
3	TOP COVER TAPE		1	PET		
4	REEL		1	POLYSTYRENE		




極数 NO. OF POS.	A	B	C	D	H
6	5.5	-	12.0	18.4	2.50
10	5.5	-	12.0	18.4	3.20
12	5.5	-	12.0	18.4	3.55
16	7.5	-	16.0	22.4	4.25
18	7.5	-	16.0	22.4	4.60
20	7.5	-	16.0	22.4	4.95
24	7.5	-	16.0	22.4	5.65
30	7.5	-	16.0	22.4	6.70
34	7.5	-	16.0	22.4	7.40
40	11.5	-	24.0	30.4	8.45
42	11.5	-	24.0	30.4	8.80
44	11.5	-	24.0	30.4	9.15
46	11.5	-	24.0	30.4	9.50
48	11.5	-	24.0	30.4	9.85
50	11.5	-	24.0	30.4	10.20
54	11.5	-	24.0	30.4	10.90
60	11.5	-	24.0	30.4	11.95


※この表は2ページ目のみ適用
 ※THIS CHART IS APPLICABLE TO SHEET-2 ONLY.

注記
NOTE

- 梱包数量 : 15000 個/リール
PACKING QUANTITY : 15000 ea/reel
- 納入時のリール巻き方向
REELING DIRECTION IN DELIVERY






- 引出し方向
USER DIRECTION OF FEED



- 型番 P/N 14 5861 XXX 024 829 +
極数 NO. OF POS.

※この注記の1~3は2ページ目のみ適用
 ※THIS NOTES 1 TO 3 ARE APPLICABLE TO SHEET-2 ONLY.



ROHS規制対応
COMPLIANT WITH
ROHS REGULATIONS

TOLERANCE / 一般公差(S)		PRODUCT SPEC / 製品規格		REFER TO SHEET 1/2					
X < 10	±0.2	UNIT	ANGLE	NO.	EDN/DCN	DATE	ISSUE	CHECKED	APPROVED
10 ≤ X < 30	±0.25	mm	3RD	PART NAME / 品名					
30 ≤ X	±0.3	SCALE	DATE	SERIES 5861 PLUG EMBOSS TAPE ASSY SMT					
ANGLE / 角度	±3°	3 : 1	2015/09/15	0.35mm PITCH BOARD TO BOARD H=0.6 W=1.95					
DRAWN	DESIGNED	CHECKED	APPROVED	PART NO. / 型番					
M. TAKAHASHI	K. HIRATA	K. YAMANE	T. SASAKI	14 5861 XXX 024 829 +					
KYOCERA				DWG NO. / 図番		SHEET/REV			
				BJS 5861005		12/21 P			