








SECT. X-X


極数 NO. OF POS.	A	B	C
31	15.0	21.0	20.0
32	15.5	21.5	20.5
33	16.0	22.0	21.0
34	16.5	22.5	21.5
35	17.0	23.0	22.0
36	17.5	23.5	22.5
37	18.0	24.0	23.0
38	18.5	24.5	23.5
39	19.0	25.0	24.0
40	19.5	25.5	24.5
41	20.0	26.0	25.0
42	20.5	26.5	25.5
43	21.0	27.0	26.0
44	21.5	27.5	26.5
45	22.0	28.0	27.0
46	22.5	28.5	27.5
47	23.0	29.0	28.0
48	23.5	29.5	28.5
49	24.0	30.0	29.0
50	24.5	30.5	29.5

注 記
NOTE

- ① コンタクトテールの最大浮き0.1mmとする。
CONTACT TAIL
HEIGHT SHALL BE 0.1mm MAX.
- ② 適用FPC, FFC寸法は1か2を選択のこと。
SELECT AN APPLICABLE FPC, FFC
FROM 1 OR 2.
- ③ Rは, FPCの導体部に掛からないこと。
R SHOULD NOT OVERLAP CONDUCTOR.


推奨基板取付寸法(コネクタ搭載側)
MOUNTING LAYOUT(CONN. MOUNTING SIDE)

	FPC		FFC	
	1	2	1	2
M	0.5±0.12	0.5±0.1	0.5±0.1	0.5±0.08
P	0.5±0.02	0.5±0.05	0.5±0.03	0.5±0.05
A	A±0.03	A±0.05	A±0.03	A±0.05
W	W±0.07	W±0.07	W±0.07	W±0.07
WD	0.35 ^{+0.04} _{-0.03}	0.35±0.05	0.3 ^{+0.05} _{-0.02}	0.3 ^{+0.05} _{-0.02}

適用FPC, FFC寸法
APPLICABLE FPC, FFCROHS規制対応
COMPLIANT WITH
ROHS REGULATIONS

TOLERANCE / 一般公差(S)		PRODUCT SPEC / 製品規格		C	DCN20571	2020/08/05	Y. MANBA		Y. FUJII
X < 10 ±0.2 10 ≤ X < 30 ±0.25 30 ≤ X ±0.3		UNIT mm ANGLE 3RD		B	DCN19755	2019/08/05	Y. SAMPEI	N. KITAGAWA	Y. FUJII
				0	EDN-843	2003/10/28	C. YAMATO		K. ONO
				NO.	EDN/DCN	DATE	ISSUE	CHECKED	APPROVED
ANGLE / 角度 ±3°		SCALE NTS DATE 2003/10/28		PART NAME / 品名 SERIES 6274 FPC/FFC ASSY ST SMT 0.5mm PITCH ZIF CONNECTOR					
DRAWN C. YAMATO	DESIGNED C. YAMATO	CHECKED	APPROVED K. ONO	PART NO. / 製番 04 6274 0XX X00 800 +					
		DWG NO. / 図番 BJS 6274020		SHEET/REV 1/2 C					

KYOCERA




ROHS規制対応
COMPLIANT WITH
ROHS REGULATIONS

NO.	DESCRIPTION	PART NO.	QTY	MATERIAL	DRW NO.	REMARKS
1	CONNECTOR	04 6274 0XX X00 800 +	1000			00 6274 0XX X00 800 +
2	EMBOSSED TAPE		1	POLYSTYRENE		
3	TOP COVER TAPE		1	POLYSTYRENE		
4	REEL		1	POLYSTYRENE		


注 記
NOTE

1. 梱包数量 : 1000 個/リール
PACKING QUANTITY : 1000 ea/reel

2. 納入時のリール巻き方向
REELING DIRECTION
IN DELIVERY



3. 引出し方向
USER DIRECTION OF FEED



4. 型 番
P/N 04 6274 0XX X00 800 +

極 数
NO. OF POS.

0 : 正千鳥
STAGGER TYPE.

1 : 逆千鳥
REVERSE TYPE.

めっき
PLATING

+ : Sn-Cu 2μmMIN.

※この注記の1～3は2ページ目にお適用
※THIS NOTES 1 TO 3 ARE APPLICABLE TO SHEET-2 ONLY.

極 数 NO. OF POS.	A	B	C	D
31	20.2	40.4	44.0	50.4
32	20.2	40.4	44.0	50.4
33	20.2	40.4	44.0	50.4
34	20.2	40.4	44.0	50.4
35	20.2	40.4	44.0	50.4
36	20.2	40.4	44.0	50.4
37	20.2	40.4	44.0	50.4
38	20.2	40.4	44.0	50.4
39	20.2	40.4	44.0	50.4
40	20.2	40.4	44.0	50.4
41	20.2	40.4	44.0	50.4
42	20.2	40.4	44.0	50.4
43	20.2	40.4	44.0	50.4
44	20.2	40.4	44.0	50.4
45	20.2	40.4	44.0	50.4
46	20.2	40.4	44.0	50.4
47	20.2	40.4	44.0	50.4
48	20.2	40.4	44.0	50.4
49	20.2	40.4	44.0	50.4
50	20.2	40.4	44.0	50.4

※この表は2ページ目にお適用
※THIS CHART IS APPLICABLE TO
SHEET-2 ONLY.

※生産対応可能極数については、
営業部にご確認願います。
PLEASE ASK SALES DEPARTMENT
WHAT NUMBER OF CONTACT
CAN BE PRODUCED.

TOLERANCE / 一般公差 (S)		PRODUCT SPEC / 製品規格									
X <10 10 ≤ X <30 30 ≤ X	±0.2 ±0.25 ±0.3	UNIT		ANGLE		REFER TO SHEET		1/2			
		mm		3RD		NO.	EDN/DCN	DATE	ISSUE	CHECKED	APPROVED
		SCALE		DATE		PART NAME / 品名					
ANGLE / 角度		NTS		2003/10/28		SERIES 6274 FPC/FFC ASSY ST SMT TAPING					
DRAWN	DESIGNED	CHECKED	APPROVED		PART NO. / 型番						
C. YAMATO	C. YAMATO		K. ONO		04 6274 0XX X00 800 +						
					DWG NO. / 図番				SHEET/REV		
					BJS 6274020				2/2 C		

KYOCERA