








基板取付け寸法
MOUNTING LAYOUT



SECT. D-D
(S=20:1)



NO.	DESCRIPTION	PART NO.	QTY	MATERIAL	DRW NO.	REMARKS
1	INSULATOR		1	HEAT RESISTING PLASTIC		UL94V-0 COLOR: IVORY (NATURAL)
2	CONTACT		N	PHOS-BRONZE		t=0.2 Sn-Cu
3	ANCHOR PLATE		2	BRASS		t=0.2 Sn-Cu

極 数 NO. OF POS.	A	B	C
5	2.0	4.4	3.1
6	2.5	4.9	3.6
7	3.0	5.4	4.1
8	3.5	5.9	4.6
9	4.0	6.4	5.1
10	4.5	6.9	5.6
11	5.0	7.4	6.1
12	5.5	7.9	6.6
13	6.0	8.4	7.1
14	6.5	8.9	7.6
15	7.0	9.4	8.1
16	7.5	9.9	8.6
17	8.0	10.4	9.1
18	8.5	10.9	9.6
19	9.0	11.4	10.1
20	9.5	11.9	10.6
21	10.0	12.4	11.1
22	10.5	12.9	11.6
23	11.0	13.4	12.1
24	11.5	13.9	12.6
25	12.0	14.4	13.1
26	12.5	14.9	13.6
27	13.0	15.4	14.1
28	13.5	15.9	14.6
29	14.0	16.4	15.1
30	14.5	16.9	15.6

※この表は1, 2ページ目にのみ適用
※THIS CHART IS APPLICABLE TO
SHEET-1 AND SHEET-2 ONLY.

ROHS規制対応
COMPLIANT WITH
ROHS REGULATIONS

TOLERANCE / 一般公差 (S)		PRODUCT SPEC / 製品規格		C	DCN22066	2022/01/31	N. KITAGAWA	N. NAKAJIMA	A. TSUNEMURA
				B	DCN20662	2020/07/01	A. MURATA	N. KITAGAWA	M. YOSHIDA
				O	EDN-622	2008/09/10	K. MURAKAMI	A. TSUNEMURA	T. SATOH
				NO.	EDN/DCN	DATE	ISSUE	CHECKED	APPROVED
				PART NAME / 品名					
				SERIES 6284 FPC FFC ASSY					
				0.5mmPITCH CONNECTOR H=1.5 LIF TYPE					
				PART NO. / 型番					
				04 6284 OXX 002 800 +					
				DWG NO. / 図番					
				BJS 6284022					
				SHEET / REV					
				1 / 3 C					



注 記
NOTE


1. コンタクトテール及び固定金具は基板より
最大浮き0.1mmとする。
CONTACT TAIL AND ANCHOR PLATE
HEIGHT SHALL BE 0.1MAX.

② 適用FPC／FFC寸法は1か2を選択のこと。
SELECT AN APPLICABLE
FPC/FFC FROM 1 OR 2.

※この注記は1，2ページ目にのみ適用

※THIS NOTES IS APPLICABLE TO SHEET-1 AND SHEET-2 ONLY.

	FPC		FFC	
	1	2	1	2
M	0.5±0.12	0.5±0.1	0.5±0.1	0.5±0.08
P	0.5±0.02	0.5±0.05	0.5±0.03	0.5±0.05
A	A±0.03	A±0.05	A±0.03	A±0.05
W	W±0.07	W±0.07	W±0.07	W±0.07
Wp	0.35 ^{+0.04} _{-0.03}	0.35±0.05	0.3 ^{+0.05} _{-0.02}	0.3 ^{+0.05} _{-0.02}




適用FPC／FFC寸法
APPLICABLE FPC/FFC

NO.	DESCRIPTION	PART NO.	QTY	MATERIAL	DRW NO.	REMARKS
-----	-------------	----------	-----	----------	---------	---------

FPC構成
FPC STRUCTURE


(推奨仕様)



表面処理 SURFACE TREATMENT
ウィスカ対策Sn系鉛フリーめっき
Sn-BASED LEAD-FREE PLATING
AGAINST WHISKER

FFC構成
FFC STRUCTURE


(推奨仕様)



表面処理 SURFACE TREATMENT
ウィスカ対策Sn系鉛フリーめっき
Sn-BASED LEAD-FREE PLATING
AGAINST WHISKER

ROHS規制対応
COMPLIANT WITH
ROHS REGULATIONS

TOLERANCE / 一般公差 (S)		PRODUCT SPEC / 製品規格							
X < 10 ±0.2 10 ≤ X < 30 ±0.25 30 ≤ X ±0.3		UNIT mm ANGLE 3RD		REFER TO SHEET 1/3					
ANGLE / 角度 ±3°		SCALE NTS DATE 2008/09/10		NO.	EDN/DCN	DATE	ISSUE	CHECKED	APPROVED
DRAWN M. TAKAHASHI DESIGNED K. MURAKAMI CHECKED A. TSUNEMURA APPROVED T. SATOH		PART NAME / 品名 SERIES 6284 FPC FFC ASSY 0.5mm PITCH CONNECTOR H=1.5 LIF TYPE		PART NO. / 型番 04 6284 OXX 002 800 +					
		DWG NO. / 図番 BJS 6284022		SHEET / REV 2/3 C					



樞 NO. OF POS.	A	B	C	D
5	7.5	—	16.0	22.4
6	7.5	—	16.0	22.4
7	7.5	—	16.0	22.4
8	7.5	—	16.0	22.4
9	11.5	—	24.0	30.4
10	11.5	—	24.0	30.4
11	11.5	—	24.0	30.4
12	11.5	—	24.0	30.4
13	11.5	—	24.0	30.4
14	11.5	—	24.0	30.4
15	11.5	—	24.0	30.4
16	11.5	—	24.0	30.4
17	11.5	—	24.0	30.4
18	11.5	—	24.0	30.4
19	11.5	—	24.0	30.4
20	11.5	—	24.0	30.4
21	11.5	—	24.0	30.4
22	11.5	—	24.0	30.4
23	11.5	—	24.0	30.4
24	11.5	—	24.0	30.4
25	14.2	28.4	32.0	38.4
26	14.2	28.4	32.0	38.4
27	14.2	28.4	32.0	38.4
28	14.2	28.4	32.0	38.4
29	14.2	28.4	32.0	38.4
30	14.2	28.4	32.0	38.4

*THIS NOTES 1 TO 3 ARE APPLICABLE TO SHEET-3 ONLY.

TOLERANCE / 一般公差 (S)		PRODUCT SPEC / 製品規格							
$10 \leq X < 30$ $30 \leq X$		± 0.2 ± 0.25 ± 0.3		UNIT mm	ANGLE 3RD		REFER TO SHEET 1/3		
ANGLE / 角度 $\pm 3^\circ$		SCALE 2 : 1		DATE 2008/09/10		NO. EDN/DCN		DATE	ISSUE
						PART NAME / 品名		CHECKED	
						SERIES 6284 EMOSS TAPE ASSY RA SMT		APPROVED	
						FPC/FFC ASSY			
DRAWN M. TAKAHASHI		DESIGNED K. MURAKAMI		CHECKED A. TSUNEMURA		APPROVED T. SATOH		PART NO. / 型番 04 6284 0XX 002 800 +	
				DWG NO. / 図番 BJS 6284022				SHEET/REV 13/3 C	