## 1. 適用範囲

本仕様書は、5690シリーズ コネクターの組立製品のエンボステープ梱包 に適用する。

- 2. 対象製品型番 2/2頁参照
- 3. 梱包副資材 2/2頁参照
- 4. 梱包方法
  - (1) エンボステープ梱包
    - ①エンボステープポケットへ製品を図の向きに1個ずつ詰め、 トップテープを上面にヒートシーリングしてリールに巻き取る。
    - ②リール巻き仕様

図のようにエンボステープの巻き始め200mm をダミーとして 巻き取り芯に粘着テープで止める。

製品を350個実装した後、更に巻き終わり400mm以上のダミー部を設ける。

最後にエンボステープを図の様に粘着テープ止めし、現品票を貼付する。

- (2) 外装箱梱包
- ①緩衝材を十字に敷き詰め、製品を詰めたリールを外装箱に段重ね 収納する。4隅の緩衝材は柱状を詰めてから上部を覆う。
- ②最上部は中敷板で蓋をしてテープで止める。
- ③外装箱の封は市販粘着テープで行う。
- ④現品票を側面に貼付する

現品票は京セラ指定のバーコード表示を原則とする。

〈現品票記入項目〉

製品型番、製品ロット番号、数量

## 1. Scope

This specifies embossed packaging for assembly of connector of series 5690.

- 2. Part number of applicable products (See page 2/2)
- 3. Packaging material (See page 2/2)
- 4. Packaging method
- (1) Packaging of embossed tape (Fig.1)
  - ①Put a connector into the pocket, seal the top tape, and reel it.
  - ②Fix the start of the top tape with an adhesive tape.

Let the start of the embossed tape 200mm be no components Put 350pcs.connectors into the pocket.

Let the end of the embossed tape 400mm be no components.

Fix the end of the tape with an adhesive tape as shown in (Fig.2) and stick a slip.

- (2) Packaging of outer carton (Fig. 2)
- ① Put the cushioning material crosswise and package the reels packed with products in a step stack on the exterior box

  To store it. The cushioning materials at the four corners fill the columnar shape and cover the upper part.
- ② The top closes the cap in middle planking and stops it with tape.
- ③ I perform the seal of the decoration box with commercial adhesive tape.
- ④ I attach an item on display vote on the side.

Bar code form of KYOCERA Corporation is standard.

A slip be filled in the customer's part number, lot number and Q'ty.

REV.	CONTENTS	EDN/DCN	DATE	ISSUE	CHECKED	APPROVED
O	INITIAL VERSION	EDN-059	13/01/24	Y,Nakamura	H,Suzuki	N,Ninomiya
D	Specifications change	DCN-394	15/07/24	Y,Nakamura	M,Yoshida	N,Hayashi
E	Specifications change	DCN-133	17/02/02	Y,Nakamura	K,Miyamoto	A,Mizukoshi
F	Specifications change	DCN-761	17/08/02	Y,Nakamura	K,Miyamoto	A,Mizukoshi

梱包仕様 PACKING SPECIFICATION Ser			5 6 9 0 ASSEMBLY OF EME	NO. 305-03-969		REV F	(2/2)	
2.対象型番		3.梱包副資材			Q'ty	リール	箱小	箱大
P/N	PACKAGING MATERIAL		P/N	Size	Pos.	Reel	PAC. S	PAC. L
14 5690 *** 0** 829 +* Embossed tape of 44/56mm wide		98 5690 *** 00* 000	24Pitch	30~40P(44W)	350	700	1,400	
24 5690 *** 1** 829 +*	Top tape of 44/56mm wide		95 9300 0018 60 014/015	T0.06×38.5/50.5mm wide	60~80P(56W)	350	350	1,050
24 5690 *** 0** 829 +*	Emboss reel of 44/56mm wide		95 9300 0018 40 135/136	φ380 : 49.5/61.5mm wide				
	Outer ca	rton (Small)	95 9300 0018 20 114	385mm×385mm×H125mm				
	Outer ca	rton (Large)	95 9300 0018 20 115	385mm×385mm×H250mm				
Fig 1				Fig 2				
	リ <b>ー</b> ル R				>			

