

Datasheet of SAW Duplexer


1814 Band25 Unbalanced

KYOCERA Part No. : SD18 1882R8UUC1


Rating

Items	Rating	Unit	Note
Operating Temperature Range	-30 to +85	deg.C	
Storage Temperature Range	-40 to +85	deg.C	
Max Input Power (Tx port)	+29	dBm	5,000hours, Ta=50deg.C, CW
Tx Port Nominal Impedance	50	ohm	Unbalance
Ant. Port Nominal Impedance	50//3.6nH	ohm	Unbalance
Rx Port Nominal Impedance	50	ohm	Unbalance


Dimensions



Recommendable Land Pattern



Measurement Circuit




Electrical Characteristics

Items		Frequency (MHz)			Characteristics			Unit	Note
					min.	typ.	max.		
Tx to Ant	Nominal Center Frequency	-			1882.5			MHz	
	Insertion Loss	1850	to	1911	-	1.8	2.5	dB	
		1911	to	1915	-	2.3	4.0	dB	
	Ripple (any 5MHz)	1850.48	to	1914.52	-	0.6	2.0	dB	
	VSWR	1850.48	to	1914.52	-	1.7	2.0	-	
								-	
	Absolute Attenuation	10	to	728	30	50	-	dB	
		728	to	768	44	48	-	dB	
		869	to	894	44	49	-	dB	
		1226	to	1250	43	46	-	dB	
		1559	to	1563	43	53	-	dB	
		1565.4	to	1573.4	43	53	-	dB	
		1573.4	to	1577.5	43	53	-	dB	
		1577.5	to	1585.4	43	53	-	dB	
		1597.6	to	1605.9	43	51	-	dB	
		1605.866	to	1680	30	43	-	dB	
		1930	to	1995	40	55	-	dB	-20 to +85deg.C
		2110	to	2200	39	46	-	dB	
		2350	to	2360	36	41	-	dB	
		2400	to	2700	33	37	-	dB	
		3700	to	3830	25	29	-	dB	
		5150	to	5350	20	24	-	dB	
		5254	to	5455	20	24	-	dB	
		5520	to	5845	20	22	-	dB	
Ant to Rx	Nominal Center Frequency	-			1962.5			MHz	
	Insertion Loss	1930.48	to	1994.52	-	2.7	3.5	dB	
	Ripple (any 5MHz)	1930.48	to	1994.52	-	0.6	2.0	dB	
	VSWR	1930.48	to	1994.52	-	1.4	2.0	-	
								-	
	Absolute Attenuation	1	to	1850	40	54	-	dB	
		80			50	104	-	dB	
		699	to	716	40	67	-	dB	
		777	to	787	40	65	-	dB	
		814	to	849	40	63	-	dB	
		1850	to	1915	45	53	-	dB	
		2055	to	2080	25	29	-	dB	
		2080	to	6000	40	48	-	dB	
		2305	to	2315	40	53	-	dB	
		2400	to	2500	40	53	-	dB	
		4900	to	5950	40	56	-	dB	
		5610	to	5845	48	56	-	dB	
		5790	to	5985	40	55	-	dB	
Tx to Rx	Isolation	1574	to	1577	40	72	-	dB	
		1850.25	to	1910	55	58	-	dB	
		1910	to	1914.75	50	58	-	dB	
		1930.25	to	1994.75	45	57	-	dB	-20 to +85deg.C
		1930.48	to	1989.52	50	57	-	dB	-10 to +85deg.C
		3700	to	3820	20	58	-	dB	
		5550	to	5850	20	51	-	dB	



Electrical Characteristics

[Tx to Ant]





Electrical Characteristics

[Ant to Rx]









Electrical Characteristics

[Tx to Rx]




Electrical Characteristics



Tape & Reel Specification


[Tape]




Unit : mm

Part	Dimension
A	1.7±0.1
B	2.05±0.10
C	8.0±0.2
D	3.50±0.05
E	1.75±0.10
F	4.0±0.1
G	4.0±0.1
H	2.00±0.05
φJ	1.5+0.1/-0
φK	0.80±0.05
R	0.2 Max
W	0.7±0.1
T	0.20±0.05

W : Dimension is depth of pockets.



[Reel]



Unit : mm

Part	Dimension
A	178 ± 2
B	60 ± 2
C	13.0 ± 0.2
D	21.0 ± 0.8
E	2.0 ± 0.5
R	1
W	9.5 ± 1.0
T	2.0 ± 0.2

Notice

1. Characteristics described in this datasheet are for references specifications shall be based on written documents agreed by each party.
2. Contents in this datasheet are subject to change without notice. It is recommended to confirm the latest information at the time of usage. Also, this datasheet is revised once a year. We may not be able to accept requests based on old datasheets.
3. Products in this datasheet are intended to be used in general electronic equipment such as office equipment, audio and visual equipment, communication equipment, measurement instrument and home appliances. It is absolutely recommended to consult with our sales representatives in advance upon planning to use our products in applications which require extremely high quality and reliability such as aircraft and aerospace equipment, traffic systems, safety systems, power plant and medical equipment including life maintenance systems.
4. Even though we strive for improvements of quality and reliability of products, it is requested to design with enough safety margin in equipment or systems in order not to threaten human lives directly or damage human bodies or properties by an accidental result of products.
5. It is requested to design based on guaranteed specifications for such as maximum ratings, operating voltage and operating temperature. It is not the scope of our guarantee for unsatisfactory results due to misuse or inadequate usage of products in the datasheet.
6. Operation summaries and circuit examples in this datasheet are intended to explain typical operation and usage of the product. It is recommended to perform circuit and assembly design considering surrounding conditions upon using products in this datasheet.
7. Technical information described in this datasheet is meant to explain typical operations and applications of products, and it is not intended to guarantee or license intellectual properties or other industrial rights of the third party or Kyocera.
8. Trademarks, logos and brand names used in this datasheet are owned by Kyocera or the corresponding third party.
9. Certain products in this datasheet are subject to the Foreign Exchange and Foreign Trade Control Act of Japan, and require the license from Japanese Government upon exporting the restricted products and technical information under the law. Besides, it is requested not to use products and technical information in the datasheet for the development and/or manufacture of weapons of mass destruction or other conventional weapons, nor to provide them to any third party with the possibility of having such purposes.
10. It is prohibited to reprint and reproduce a part or whole of this datasheet without permission.