

Series	Size
<u>KGM</u>	JIS0402/EIA01005 – JIS3225/EIA 1210

Series	Size
<u>KGM</u>	JIS0402/EIA01005 – JIS3225/EIA 1210

Crystal Devices	Series	Size	Frequency
Image processor	CX2016DB	2016	27MHz
Wi-Fi, Bluetooth®	CX1210SB	1210	48MHz
Wi-Fi, Bluetooth®	CX1210SB	1210	76.8MHz
Wi-Fi, Bluetooth®	CX1612DB	1612	48MHz
GNSS/GPS	KT1612A	1612	26MHz
GNSS/GPS	KT2016K	2016	26MHz
USB	CX2016DB	2016	48MHz

Crystal Devices	Series	Size	Frequency
Image processor	CX2016DB	2016	27MHz
Wi-Fi, Bluetooth®	CX1210SB	1210	48MHz
Wi-Fi, Bluetooth®	CX1210SB	1210	76.8MHz
Wi-Fi, Bluetooth®	CX1612DB	1612	48MHz
GNSS/GPS	KT1612A	1612	26MHz
GNSS/GPS	KT2016K	2016	26MHz
USB	CX2016DB	2016	48MHz

FPC/FFC Connectors		
Series	Pitch (mm)	Lock type
<u>6866</u>	0.2	Front Flip
<u>6844</u>	0.3	Front Flip
<u>6293</u>	0.3	Back Flip
<u>6287</u>	0.4	Front Flip
<u>6824</u>	0.4	Non-ZIF
<u>6810</u>	0.5	One-action

FPC/FFC Connectors		
Series	Pitch (mm)	Lock type
<u>6866</u>	0.2	Front Flip
<u>6844</u>	0.3	Front Flip
<u>6293</u>	0.3	Back Flip
<u>6287</u>	0.4	Front Flip
<u>6824</u>	0.4	Non-ZIF
<u>6810</u>	0.5	One-action

SuperCap™	
Series	Capacitance Range
<u>SCC</u>	1F – 3000F
<u>SCM</u>	0.33F – 15F

SuperCap™	
Series	Capacitance Range
<u>SCC</u>	1F – 3000F
<u>SCM</u>	0.33F – 15F

Battery Connectors			
Series	Pitch (mm)	Current Rated	Voltage Rating
<u>9155-000</u>	2.5	3A/Contact	125VAC

Battery Connectors			
Series	Pitch (mm)	Current Rated	Voltage Rating
<u>9155-000</u>	2.5	3A/Contact	125VAC

Polymer Capacitors

Series	Capacitance Range
TCJ	0.47 - 680 μ F
TCN	4.7 μ F – 1500 μ F

Polymer Capacitors

Series	Capacitance Range
TCJ	0.47 - 680 μ F
TCN	4.7 μ F – 1500 μ F

- Patch Antennas

Series	Size (mm)
<u>1001039</u>	25.0 × 25.0 × 4.5
<u>1001044</u>	12.8 × 12.8 × 4.0

- Patch Antennas

Series	Size (mm)
<u>1001039</u>	25.0 × 25.0 × 4.5
<u>1001044</u>	12.8 × 12.8 × 4.0

Series	Applicable Standard
<u>5138</u>	microSD™

Series	Applicable Standard
<u>5138</u>	microSD™

Series	Pitch (mm)	Stacking Height (mm)
<u>5814</u>	0.3	0.6
<u>5861</u>	0.35	0.6
<u>5863</u>	0.35	0.8
<u>5843</u>	0.35	0.8
<u>7129</u>	0.35	0.7
<u>5804</u>	0.4	0.9/1.5/2.0
<u>5806</u>	0.4	0.6
<u>5655</u>	0.5	4.0 – 7.0

Series	Pitch (mm)	Stacking Height (mm)
<u>5814</u>	0.3	0.6
<u>5861</u>	0.35	0.6
<u>5863</u>	0.35	0.8
<u>5843</u>	0.35	0.8
<u>7129</u>	0.35	0.7
<u>5804</u>	0.4	0.9/1.5/2.0
<u>5806</u>	0.4	0.6
<u>5655</u>	0.5	4.0 – 7.0

Series	Pitch (mm)	Height (mm)
<u>6893</u>	0.5	2.8
<u>5861</u>	0.35	0.6

Series	Pitch (mm)	Height (mm)
<u>6893</u>	0.5	2.8
<u>5861</u>	0.35	0.6