

MLCC

Series	Size
KGM	JIS0402/EIA01005 – JIS3225/EIA 1210

Crystal Devices

	Series	Size	Frequency
Image processor	CX2016DB	2016	27MHz
Wi-Fi, Bluetooth®	CX1210SB	1210	48MHz
Wi-Fi, Bluetooth®	CX1210SB	1210	76.8MHz
Wi-Fi, Bluetooth®	CX1612DB	1612	48MHz
GNSS/GPS	KT1612A	1612	26MHz
GNSS/GPS	KT2016K	2016	26MHz
USB	CX2016DB	2016	48MHz

FPC/FFC Connectors

Series	Pitch (mm)	Lock type
6866	0.2	Front Flip
6844	0.3	Front Flip
6293	0.3	Back Flip
6287	0.4	Front Flip
6824	0.4	Non-ZIF
6810	0.5	One-action

SuperCap™

Series	Capacitance Range
SCC	1F – 3000F
SCM	0.33F – 15F

Battery Connectors

Series	Pitch (mm)	Current Rated	Voltage Rating
9155-000	2.5	3A/Contact	125VAC

Polymer Capacitors

Series	Capacitance Range
TCJ	0.47 - 680 μ F
TCN	4.7 μ F – 1500 μ F

Patch Antennas

Series	Size (mm)
1001039	25.0 × 25.0 × 4.5
1001044	12.8 × 12.8 × 4.0

Memory Card Connectors

Series	Applicable Standard
5138	microSD™

Board to Board Connectors

Series	Pitch (mm)	Stacking Height (mm)
5814	0.3	0.6
5861	0.35	0.6
5863	0.35	0.8
5843	0.35	0.8
7129	0.35	0.7
5804	0.4	0.9/1.5/2.0
5806	0.4	0.6
5655	0.5	4.0 – 7.0

FPC/FFC, Board to Board Connectors

Series	Pitch (mm)	Height (mm)
6893	0.5	2.8
5861	0.35	0.6