

* Click the series number to check the product information

Control Button, Stick

FPC/FFC Connectors

Height: 0.85~5.32mm



● 0.5mm Pitch

6809 Ease of use, Robust, Front-lock

6811 Robust, Front-lock

6284 Non-ZIF

6806 Ease of use, Front-lock

6892 AOI-compatible, Front-lock

6244 Vertical, Non-ZIF

Battery

Board to Board Connectors

Stacking Height: 0.6~0.7mm



● 0.35mm Pitch

7129 Power 10A, Space-saving

Speaker, Mic., Sensor

FPC/FFC Connectors

Height: 0.85~1.75mm



● 0.3mm Pitch

6293 Lower-profile, Back-lock

6844 Space-saving, Front-lock

● 0.4mm Pitch

6824 Space-saving, Non-ZIF

● 0.5mm Pitch

6277 Low pin count, Back-lock

6298 Low pin count, Back-lock

6809 Ease of use, Robust, Front-lock

6811 Robust, Front-lock

6284 Non-ZIF

6806 Ease of use, Front-lock

Board to Board Connectors

Stacking Height: 0.7~2.0mm



● 0.35mm Pitch

7129 Power 10A, Space-saving

5861 Power 5A, Lower-profile

5843 Stacking height variations

● 0.4mm Pitch

5804 Stacking height variations

Vibrator

Wire to Board Connectors

Height: 0.9~3.61mm



8041 0.9mm Pitch


8040 1.0mm Pitch

8005 1.27mm Pitch

Main – Sub. PCB (I/O)

FPC/FFC Connectors

Height: 0.85~5.32mm



● 0.3mm Pitch

6293 Lower-profile, Back-lock

6844 Space-saving, Front-lock

● 0.4mm Pitch

6824 Space-saving, Non-ZIF

● 0.5mm Pitch

6809 Ease of use, Robust, Front-lock

6811 Robust, Front-lock

6284 Non-ZIF

6806 Ease of use, Front-lock

6892 AOI-compatible, Front-lock

6244 Vertical, Non-ZIF