

* Click the series number to check the product information

Main – Sub. PCB

FPC/FFC Connectors

Height: 0.85~0.95mm



- 0.2mm Pitch
6866 Space-saving, Front-lock
- 0.3mm Pitch
6293 Lower-profile, Back-lock
6844 Space-saving, Front-lock
- 0.5mm Pitch
6277 Low pin count, Back-lock
6298 Low pin count, Back-lock

Board to Board Connectors

Stacking Height: 0.6mm



- 0.35mm Pitch
5861 Power 5A, Lower-profile
- 0.4mm Pitch
5806 Space-saving

Speaker, Mic., Sensor

FPC/FFC Connectors

Height: 0.85~0.95mm



- 0.2mm Pitch
6866 Space-saving, Front-lock
- 0.3mm Pitch
6293 Lower-profile, Back-lock
6844 Space-saving, Front-lock
- 0.5mm Pitch
6277 Low pin count, Back-lock
6298 Low pin count, Back-lock

Board to Board Connectors

Stacking Height: 0.6mm



- 0.35mm Pitch
5861 Power 5A, Lower-profile
- 0.4mm Pitch
5806 Space-saving

Display (OLED, LCD)

FPC/FFC Connectors

Height: 0.85~0.95mm



- 0.2mm Pitch
6866 Space-saving, Front-lock
- 0.3mm Pitch
6293 Lower-profile, Back-lock
6844 Space-saving, Front-lock
- 0.5mm Pitch
6277 Low pin count, Back-lock
6298 Low pin count, Back-lock

Board to Board Connectors

Stacking Height: 0.6mm



- 0.35mm Pitch
5861 Power 5A, Lower-profile
- 0.4mm Pitch
5806 Space-saving

Battery, Wireless Charge

Board to Board Connectors

Stacking Height: 0.7mm



- 0.35mm Pitch
7129 Power 10A, Space-saving

