















車載用 / Automotive Applications

Series	周波数範囲 Frequency Range (MHz)	電源電圧 Supply Voltage (V)	外形寸法 Dimensions LxWxH (mm)
MC2016Z (X type) カタログ(pdf/202.6KB) Catalog(pdf/160.9KB)	 0.5 to 170	1.8 / 2.5 / 3.3	2.0 × 1.6 × 0.8max.
MC2016Z (Y type) カタログ(pdf/202.1KB) Catalog(pdf/160.5KB)	 24 to 72	1.8 / 2.5 / 3.3	2.0 × 1.6 × 0.8max.
MC2520Z (X type) カタログ(pdf/202.6KB) Catalog(pdf/160.9KB)	 0.5 to 170	1.8 / 2.5 / 3.3	2.5 × 2.0 × 0.8max.
MC2520Z (Y type) カタログ(pdf/202.1KB) Catalog(pdf/160.5KB)	 24 to 72	1.8 / 2.5 / 3.3	2.5 × 2.0 × 0.8max.
MC3225Z (X type) カタログ(pdf/202.6KB) Catalog(pdf/160.9KB)	 0.5 to 170	1.8 / 2.5 / 3.3	3.2 × 2.5 × 0.8max.
MC3225Z (Y type) カタログ(pdf/202.1KB) Catalog(pdf/160.5KB)	 24 to 72	1.8 / 2.5 / 3.3	3.2 × 2.5 × 0.8max.
MC5032Z (X type) カタログ(pdf/202.6KB) Catalog(pdf/160.9KB)	 0.5 to 170	1.8 / 2.5 / 3.3	5.0 × 3.2 × 1.2max.
MC5032Z (Y type) カタログ(pdf/202.1KB) Catalog(pdf/160.5KB)	 24 to 72	1.8 / 2.5 / 3.3	5.0 × 3.2 × 1.2max.
MC7050Z (X type) カタログ(pdf/202.6KB) Catalog(pdf/160.9KB)	 0.5 to 170	1.8 / 2.5 / 3.3	7.0 × 5.0 × 1.2max.
MC7050Z (Y type) カタログ(pdf/202.1KB) Catalog(pdf/160.5KB)	 24 to 72	1.8 / 2.5 / 3.3	7.0 × 5.0 × 1.2max.
MC2016K カタログ(pdf/242.1KB) Catalog(pdf/238.1KB)	 1.5 to 160	1.8 / 2.5 / 3.3	2.0 × 1.6 × 0.8max.
MC2520K カタログ(pdf/242.1KB) Catalog(pdf/238.1KB)	 1.5 to 160	1.8 / 2.5 / 3.3	2.5 × 2.0 × 0.8max.
KC3225K カタログ(pdf/242.1KB) Catalog(pdf/238.1KB)	 1.5 to 160	1.8 / 2.5 / 3.3	3.2 × 2.5 × 0.8max.
KC5032K カタログ(pdf/242.1KB) Catalog(pdf/238.1KB)	 1.5 to 160	1.8 / 2.5 / 3.3	5.0 × 3.2 × 1.2max.
KC7050K カタログ(pdf/242.1KB) Catalog(pdf/238.1KB)	 1.5 to 160	1.8 / 2.5 / 3.3	7.0 × 5.0 × 1.2max.