

Temperature Compensated Crystal Oscillator"KT1612A series"
KYOCERA Part Number : KT1612A52000ACW18TAN

Note: This is a preliminary specification.

If you would like to know official specification and details specification, please contact us.

1.Nominal condition						
Item	SYMB.	Min.	Typ.	Max.	Unit	Conditions
Operating Temperature Range	T_use	-30	-	85	deg.C	
Storage Temperature Range	T_stg	-40	-	85	deg.C	
Supply voltage	Vcc	1.7	1.8	1.9	V	1.8V+/-0.1V
Load impedance	R1	9	10	11	kohm	
	CL	9	10	11	pF	

2.Electrical Characteristics							
Item	Electrical Specification					Conditions	
	SYMB.	Min.	Typ.	Max.	Unit		
Nominal frequency	fo	-	52.0	-	MHz		
Temp characteristics	fo_TC	-0.5	-	+0.5	$\times 10^{-6}$	Referenced to the mid point between minimum and maximum frequency value over the specified temperature range	
Load characteristics	fo_Load	-0.2	-	+0.2	$\times 10^{-6}$	10kohm+/-10%, 10 pF+/-10%	
Voltage characteristics	fo_Vcc	-0.2	-	+0.2	$\times 10^{-6}$	1.8V+/-0.1V	
Aging characteristics	fo_age	-1.0	-	+1.0	$\times 10^{-6}/\gamma$	at 25+/-2 deg.C	
Frequency tolerance	fo_tol	-2.0	-	+2.0	$\times 10^{-6}$	After 2 times reflow soldering	at 25+/-2 deg.C
Output voltage	Vpp	0.8	-	1.2	Vp-p	Clipped sine	
Current consumption	Icc	-	-	2.5	mA		
Harmonics	Hm	-	-	-5.0	dBc		

