

5.0×3.2mm for Automotive



RoHS Compliant

Features

- Crystal unit for automotive electronics
- Improved solderability
- Ceramic package
- Small and low profile
- Improved rust prevention performance
- Reflow compatible
- AEC-Q200 qualified

Applications

- ECU
- TPMS
- High-Speed Automotive Network

How to Order

CX5032SA 08000 HO P T V Z1
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
 - ② Frequency
 - ③ Load Capacitance
 - ④ Frequency Tolerance
 - ⑤ Operating Temp. Range
 - ⑥ Frequency Temp. Stability
 - ⑦ Individual Specification (STD Specification is "Z1")
- | | | | |
|-----------|---------------|----------|-----------------------|
| HO | 12 pF | P | ±50×10 ⁻⁶ |
| TV | -40 to +150°C | | ±150×10 ⁻⁶ |
- Packaging (Tape & Reel 1000 pcs./ reel)

Specifications

Item	Symbol	Specification	Units	Remarks
Frequency Range	f _{nom}	8000 to 40000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	12	pF	Please contact us for other Load Capacitance.
Frequency Tolerance	f _{tol}	±15	×10 ⁻⁶	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T _{use}	-40 to +150	°C	
Storage Temp. Range	T _{stg}	-40 to +150	°C	
Frequency Temp. Characteristics	f _{tem}	±150	×10 ⁻⁶	Freq. deviation from the value at 25°C

Please contact us for other specifications.

Table1 Motional Series Resistance


Frequency Range	Motional Series Resistance
8000 ≤ f _{nom} < 9000kHz	200Ω max.
9000 ≤ f _{nom} < 12000kHz	150Ω max.
12000 ≤ f _{nom} < 20000kHz	100Ω max.
20000 ≤ f _{nom} ≤ 40000kHz	50Ω max.

Table2 Level of Drive

Frequency Range	Level of Drive
8000 ≤ f _{nom} ≤ 40000kHz	10μW (100μW max.)

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

